



PIN ASSIGNMENT

P1	P2(WIRE COLOR)	
1	RED	0.25Q+
2	YELLOW	
3	WHITE	
4	BLUE	
5	GREEN	
6	BLACK	0.25Q-
SHELL	GND	

No	Part No:	Length (MM)
1	A15-060HDR01-2.0M	2000±30
2	A15-060HDR01-3.0M	3000±35
3	A15-060HDR01-5.0M	5000±50
5	A15-060HDR01-8.0M	8000±100
6	A15-060HDR01-10.0M	10000±150

Length and Part number:

NOTES:

1. ELECTRICAL TEST: 100% OPEN, SHORT & MISS WIRE TEST.
2. CONDUCTOR RESISTANCE: 5 OHMS MAX.
3. INSULATOR RESISTANCE: 1M OHMS MIN, DC 300V 0.01sec.
4. THIS PRODUCT MEET ROHS STANDARD ENVIRONMENTAL PROTECTION POLICY.

4	OVERMOLD	BLACK PVC 45P	NA
3	TUBE	TUBE Ø6.0*30MM Black	1PCS
2	CONN	HR10A-7P-6S Female Connector	1PCS
1	CABLE	0.250*20+0.1550*4C+FTLLER+AL+BB,JACKET:PVC COLOR:Black, OD= 5.5mm	1PCS
ITEM	PART NAME	DESCRIPTION	QY'T

			QUALITY SYMBOLS		Tolerance		REV: A						UNIT: mm		DRW BY		CHK BY		APP BY		DRAWING NO.	
			☐ :	☒ :	x.	±0.60	SCALE:	N:1	DATE:	2024/03/22	Huangmei	Jack Chen			A15-060							
			CRITICAL	MAJOR	.x	±0.40																
△	2024/03/22	NEW ISSUE	Jack Chen		.xx	±0.25																
SIDE	DATE	DESCRIPTION	APPROVER	ZERO DEFECT	S.P.C			 东莞市箐国电子有限公司 www.kinkuo.com														